

For our full product
range and spec sheets,
please visit our website.

lucent®

lucent®

Lucent Lighting UK
Limited
The Old Station House
7a Coppetts Road
London N10 1NN

Tel: +44 (0)20 8442 0880
Fax: +44 (0)20 8444 6998

info@lucent-lighting.com
www.lucent-lighting.com

GE Infusion available
in the following
Lucent downlights



GE
Lighting

ProSpex 140 - 143

- Fixed and adjustable 140mm diameter downlights
- Adjustable fittings with ProAim gear driven vertical adjustment
- Hot aiming simplifies focusing while lamp is on
- Aiming remains locked in focus throughout re-lamping
- Keyed optics ensure correct installation on reflector

140



143



ProSpex Gimbal

- Recessed trimmed or trimless directional single or multi lamp gimbal fixtures with aluminium fully directional gimbal heads
- Trimmed with minimal trim for aesthetic appearance
- 45° stop in both directions
- Anti-glare snoot(s) supplied as standard
- Lamps set high, providing glare free illumination
- Front loading louvers, glass filters and lenses
- Other colour finishes to order



ProSpex 160 - 163

- Fixed and adjustable 160mm diameter downlights
- Adjustable fittings with ProAim gear driven vertical adjustment
- Hot aiming simplifies focusing while lamp is on
- Aiming remains locked in focus throughout re-lamping
- Keyed optics ensure correct installation on reflector

160



163



ProSpex Infusion Spot

- Track mounted spotlight
- Fitted with universal track adaptor for use with three circuit tracks
- Integral driver as standard
- Tilt lock as standard
- Available in matt white, textured black, and brushed aluminium finishes.
- Die Cast aluminium construction

