# lucent




### ProSpex Soft70 Fixed






90mm (3.54") overall trim diameter. 70mm (2.76") overall trimless diameter. Available with standard trim kit or plaster-in kit for flush appearance. Family of matching products also available. Required depth height + 25mm^



070-GU-TR-65 Cut-out 79mm Ø



070-GU-TL-65 Cut-out 79mm Ø



Max Power

Lamp Base


GU10 Halogen GU10 LED 50W (Halogen) GU10

# lucent<sub>®</sub>

Project Ref:	Location Ref:	
Fixture Orc	rder Code: 070-GU – – – – – – – – – – – – – – – – – – –	65
Fixture – 070-GU	Soft70 Fixed with GU10	
Installation – TR TL	 Trim Trimless	
Body Finish – WH BK RAL	White Black Custom RAL Colour*	
Trim Finish (L WH BK RAL	(Leave blank if trimless) White Black Custom RAL Colour*	
IP Rating —	IP65	



## lucent<sub>®</sub>



LLLS Linear Spread Lens LLHS Heavy Spread Lens

#### **Technical Details**

\*Custom RAL code must be specified. Custom RAL colours can increase prices and lead times

Dimming. Whilst Lucent can offer the majority of its luminaires with various dimming options, it remains the responsibility of the specifier/installer to check and ensure compatibility of any control equipment used. Additional cabling may be required depending on the dimming protocol specified.

\*\*Bluetooth (wireless) is the communication method. The exact dimming protocol must be confirmed to allow the selection of suitable drivers or bluetooth devices.

^ Depth indicated may vary depending on lamp type used

First Fix Requirement. Luminaire comprised of fixture body with ceiling trim and installation kit, which is to be fitted into the ceiling once finished. Ensure correct alignment of the installation kit before final assembly (see luminaire instllation instructions for details)

IP Rating. Tested from underside of the ceiling

It is the policy of Lucent Lighting to continually review and improve its products and therefore reserve the right to change any details of product or withdraw specifications without prior notice.

Luminaires designed to comply with EN60598 and all other standards.

This specification sheet supersededs all previous versions.

All intellectual property rights pertaining to the product described above and to this document are owned by or licensed to Lucent Lighting Ltd.

We reserve the right to take whatever action is necessary to protect those intellectual property rights.

Please notify Lucent Lighting Ltd of any inaccuracies immediately. E&OE