

Light planning Glare Evaluation According to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	17.9	18.6	18.1	18.8	19.0	17.9	18.6	18.1	18.8	19.0
	3H	17.6	18.4	18.0	18.6	18.8	17.6	18.4	18.0	18.6	18.8
	4H	17.6	18.3	18.0	18.5	18.8	17.6	18.3	18.0	18.5	18.8
	6H	17.6	18.2	17.9	18.5	18.8	17.6	18.2	17.9	18.5	18.8
	8H	17.5	18.1	17.8	18.5	18.8	17.5	18.1	17.8	18.5	18.8
	12H	17.5	18.1	17.8	18.4	18.8	17.5	18.1	17.8	18.4	18.8
4H	2H	17.6	18.3	18.0	18.5	18.8	17.6	18.3	18.0	18.5	18.8
	3H	17.5	18.1	17.8	18.4	18.8	17.5	18.1	17.8	18.4	18.8
	4H	17.3	17.9	17.8	18.3	18.8	17.3	17.9	17.8	18.3	18.8
	6H	17.3	17.8	17.8	18.2	18.5	17.3	17.8	17.8	18.2	18.5
	8H	17.2	17.8	17.7	18.1	18.5	17.2	17.8	17.7	18.1	18.5
	12H	17.1	17.6	17.6	18.0	18.5	17.1	17.6	17.6	18.0	18.5
8H	4H	17.2	17.7	17.7	18.1	18.5	17.2	17.7	17.7	18.1	18.5
	6H	17.1	17.5	17.6	18.0	18.5	17.1	17.5	17.6	18.0	18.5
	8H	17.1	17.5	17.6	18.0	18.6	17.1	17.5	17.6	18.0	18.6
	12H	17.1	17.4	17.7	17.9	18.5	17.1	17.4	17.7	17.9	18.5
12H	4H	17.1	17.6	17.6	18.0	18.4	17.1	17.6	17.6	18.0	18.4
	6H	17.1	17.5	17.6	18.0	18.6	17.1	17.5	17.6	18.0	18.6
	8H	17.1	17.4	17.7	17.9	18.5	17.1	17.4	17.7	17.9	18.5
Variation of the observer position for the luminaire distance S											
S = 1.0H		5.4 / -10.3					5.4 / -10.3				
S = 1.5H		8.1 / -12.4					8.1 / -12.4				
S = 2.0H		10.1 / -13.0					10.1 / -13.0				
Corrected glare indices referring to 1730 lm total luminous flux											