

Light efficiency:


46 Lumen/Watt

Light quality:

CRI: 91.3

Color temperature:

3000 K



Product name:

91413-F_A-LED - LED51_3-SS-30 - 1000mA


Item number:

Edge90 Fixed/Accent - LED51/3-SS-30 - 1000mA


Delivered information for above fixture and LED combination.

Output: 618 Lumen Peak intensity: 18537 cd Power consumption: 13.5


CRI R values



TM30 C Values




Color vector graphics



Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3000 K	91.3	52.7	91.7	98.7	90.5	0.437	0.404	0.251	0.348	0.0017

Beam details



Beam angels

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
8.2°	15.8°	27.7°

Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
18537 cd	99.8%	99.7%

Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
18537lx	4634lx	2060lx	1159lx	741lx	515lx	378lx	290lx	229lx	185lx	153lx	129lx	110lx	95lx	82lx	72lx	64lx	57lx	51lx	46lx
1722.1fcd	430.5fcd	191.3fcd	107.6fcd	68.9fcd	47.8fcd	35.1fcd	26.9fcd	21.3fcd	17.2fcd	14.2fcd	12fcd	10.2fcd	8.8fcd	7.7fcd	6.7fcd	6fcd	5.3fcd	4.8fcd	4.3fcd

The above information is for 3000K colour temperature, for specific module information please see LED spec located on our website.

For information regarding other colour temperatures please refer to ies/ldt files available on the website.

Light planning Glare Evaluation According to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	3.1	3.3	3.1	3.5	3.7	3.1	3.3	3.1	3.5	3.7
	3H	2.7	3.2	3.1	3.3	3.5	2.7	3.2	3.1	3.3	3.5
	4H	2.6	3.1	3.0	3.3	3.5	2.6	3.1	3.0	3.3	3.5
	6H	2.8	3.2	3.1	3.5	3.8	2.8	3.2	3.1	3.5	3.8
	8H	2.9	3.2	3.2	3.5	3.9	2.9	3.2	3.2	3.5	3.9
	12H	2.8	3.2	3.2	3.5	3.9	2.8	3.2	3.2	3.5	3.9
4H	2H	2.6	3.1	3.0	3.3	3.5	2.6	3.1	3.0	3.3	3.5
	3H	2.5	2.9	2.9	3.2	3.6	2.5	2.9	2.9	3.2	3.6
	4H	2.4	2.7	2.8	3.1	3.6	2.4	2.7	2.8	3.1	3.6
	6H	2.6	3.0	3.1	3.3	3.7	2.6	3.0	3.1	3.3	3.7
	8H	2.7	3.1	3.2	3.4	3.8	2.7	3.1	3.2	3.4	3.8
	12H	2.7	3.0	3.2	3.4	3.9	2.7	3.0	3.2	3.4	3.9
8H	4H	2.3	2.6	2.8	3.0	3.3	2.3	2.6	2.8	3.0	3.3
	6H	2.7	2.9	3.2	3.4	3.9	2.7	2.9	3.2	3.4	3.9
	8H	2.9	3.1	3.4	3.6	4.2	2.9	3.1	3.4	3.6	4.2
	12H	3.0	3.1	3.6	3.6	4.2	3.0	3.1	3.6	3.6	4.2
12H	4H	2.2	2.5	2.7	2.9	3.4	2.2	2.5	2.7	2.9	3.4
	6H	2.8	3.0	3.3	3.5	4.1	2.8	3.0	3.3	3.5	4.1
	8H	2.9	3.1	3.5	3.6	4.2	2.9	3.1	3.5	3.6	4.2
Variation of the observer position for the luminaire distance S											
S = 1.0H		5.2 / -3.9					5.2 / -3.9				
S = 1.5H		7.9 / -4.1					7.9 / -4.1				
S = 2.0H		9.8 / -4.7					9.8 / -4.7				
Corrected glare indices referring to 618 lm total luminous flux											