
# ProSpex Plus Mini Conical Accent Trim

| | |
|---|---|
| TM65.2 | 11kgCO2e |
| TM66 | 2.3 CEAM |



90mm (3.54”) overall trim diameter. Available with standard trim kit or plaster-in kit for flush appearance. Family of matching products also available. Up to 30° tilt.




750+LED-TR
Cut-out Ø82mm
Trim Kit
Required dept height+25mm^

| | | | | |
|---|---|---|---|---|
| LED Source | LED51/3-SL | LED51/3-SL | LED51/3-SL | LED51/3-SL |
| CCT | 3000K | 3000K | 3000K | 3000K |
| Drive Current | 200mA | 200mA | 200mA | 200mA |
| Power inc Driver | 8.5W | 8.5W | 8.5W | 8.5W |
| Beam Angle | SP (12°) | MF (22°) | FL (31°) | WFL (58°) |
| Delivered Lumens | 520 | 594 | 691 | 752 |
| Delivered Intensisty cd | 6610 | 3544 | 2226 | 889 |
| Efficacy lm/w | 61 | 70 | 81 | 88 |
| Forward Volt | 36V | 36V | 36V | 36V |
| CRI | ≥90 CRI | ≥90 CRI | ≥90 CRI | ≥90 CRI |

L1 ≥75 Dwellings Compliant

L2 ≥80 Display Compliant

Apply these factors to 3000K for lumen output of other CCTs: **2200K** x 0.65 / **2400K** x 0.69 / **2700K** x 0.98 / **4000K** x 1.02.

Copyright © 2025 Lucent Lighting Ltd.

Project Ref:_____ Location Ref:_____

## Fixture Order Code: 753+LED-TR – [ ] – [ ]

**Fixture**
753+LED-TR — Plus Mini Conical Accent Trim with LED51

**Finish**
WH — White RAL 9010
BK — Black RAL 9005
RAL* — Custom RAL Colour*
ABR1 — Antique Brass
ABZ1 — Antique Bronze
PCH1 — Polished Chrome
PNK1 — Polished Nickel
PBR1 — Polished Brass

**IP Rating**
44 — IP44
54 — IP54



## Module Order Code: LED51/3 – [ ] – [ ] – SL

**LED**
LED51/3 — LED50 ONE GEN 3

**CCT**
22 (3) — 90 CRI 2200K
24 (3) — 90 CRI 2400K
27 — 90 CRI 2700K
30 — 90 CRI 3000K
40 (3) — 90 CRI 4000K

**Beam**
SP — Spot
MF — Medium Flood
FL — Flood
WFL — Wide Flood

**Output Type**
SL — Shallow Height, Low Output

(3) contact Lucent for availability

## Driver Options: [ ]

**Protocol**
S — Non-Dim
A — Analogue (0-10v)
P — Phase
D — DALI
B — Bluetooth**

## Emergency Options: [ ]

**Emergency**
E — Maintained 3hr Emergency
ED — Maintained 3hr DALI Self Test
ES — Maintained 3hr Self Test

Copyright © 2025 Lucent Lighting Ltd.

## Finish selection




Antique Brass



Antique Bronze



Polished Brass



Polished Nickel




Polished Chrome

## Accessories




Honeycomb Louvre



Diffusing Lens



Frosted Lens



Heavy Spread Lens



Linear Spread Lens

Accessories Order Code:

Louvre/Lens

| | |
|---|---|
| LL45 | Honeycomb Louvre |
| LLDF | Diffusing Lens |
| LLFR | Frosted Lens |
| LLLS | Linear Spread Lens |
| LLHS | Heavy Spread Lens |

Copyright © 2025 Lucent Lighting Ltd.

## Technical Details

*Custom RAL code must be specified. Custom RAL colours can increase prices and lead times

Dimming. Whilst Lucent can offer the majority of its luminaires with various dimming options, it remains the responsibility of the specifier/installer to check and ensure compatibility of any control equipment used. Additional cabling may be required depending on the dimming protocol specified.

**Bluetooth (wireless) is the communication method. The exact dimming protocol must be confirmed to allow the selection of suitable drivers or bluetooth devices.

^ Depth indicated is the minimum recess depth for the luminaire with a remote mounted LED driver. Installing a driver through either the luminaire cut-out or installation kit may require additional recess depth, please refer to the relevant luminaire installation instructions for further details.Data correct at time of publishing

First Fix Requirement. Luminaire comprised of fixture body with ceiling trim and installation kit, which is to be fitted into the ceiling once finished. Ensure correct alignment of the installation kit before final assembly (see luminaire instllation instructions for details)

IP Rating. Tested from underside of the ceiling

Note that the picture of the finishes provided is for illustrative purposes only. The finishes may vary in colour, texture and appearance. Contact Lucent lighting Ltd for more information.

It is the policy of Lucent Lighting to continually review and improve its products and therefore reserve the right to change any details of product or withdraw specifications without prior notice.

Luminaires designed to comply with EN60598 and all other standards.

This specification sheet supersededs all previous versions.

All intellectual property rights pertaining to the product described above and to this document are owned by or licensed to Lucent Lighting Ltd.

We reserve the right to take whatever action is necessary to protect those intellectual property rights.

Please notify Lucent Lighting Ltd of any inaccuracies immediately. E&OE