
ProSpex Plus Mini Conical Fixed Trimless

TM65.2	11kgCO2e
TM66	2.3 CEAM



80mm (3.15”) overall trimless diameter. Available with standard trim kit or plaster-in kit options. Family of matching products also available.



750+LED-TL/PCZ
Cut-out Ø82mm
Trimless Kit
Required dept height+25mm^

LED Source	LED51/3-SL	LED51/3-SL	LED51/3-SL	LED51/3-SL
CCT	3000K	3000K	3000K	3000K
Drive Current	200mA	200mA	200mA	200mA
Power inc Driver	8.5W	8.5W	8.5W	8.5W
Beam Angle	SP (12°)	MF (22°)	FL (31°)	WFL (58°)
Delivered Lumens	520	594	691	752
Delivered Intensisty cd	6610	3544	2226	889
Efficacy lm/w	61	70	81	88
Forward Volt	36V	36V	36V	36V
CRI	≥90 CRI	≥90 CRI	≥90 CRI	≥90 CRI

L1 ≥75 Dwellings Compliant

L2 ≥80 Display Compliant

Apply these factors to 3000K for lumen output of other CCTs: **2200K** x 0.65 / **2400K** x 0.69 / **2700K** x 0.98 / **4000K** x 1.02.

Copyright © 2025 Lucent Lighting Ltd.

Project Ref:_____ Location Ref:_____

Fixture Order Code: 750+LED-TL – [ ] – [ ] – [ ]

Fixture
750+LED-TL — Plus Mini Conical Fixed Trimless with LED51

Installation
750+TL — TL trimless kit
750+PCZ — PCZ Plaster kit


Finish

WH — White RAL 9010
BK — Black RAL 9005
RAL* — Custom RAL Colour*
ABR1 — Antique Brass
ABZ1 — Antique Bronze
PCH1 — Polished Chrome
PNK1 — Polished Nickel
PBR1 — Polished Brass

IP Rating
44 — IP44
54 — IP54



750+PCZ
Trimless Kit
Front fitting, full skim



750+TL
Trimless Kit
Rear fitting, partial skim

Module Order Code: LED51/3 – [ ] – [ ] – SL

LED
LED51/3 — LED50 ONE GEN 3

CCT
22 (3) — 90 CRI 2200K
24 (3) — 90 CRI 2400K
27 — 90 CRI 2700K
30 — 90 CRI 3000K
40 (3) — 90 CRI 4000K

Beam
SP — Spot
MF — Medium Flood
FL — Flood
WFL — Wide Flood

Output Type
SL — Shallow Height, Low Output

(3) contact Lucent for availability

Driver Options: [ ]

Protocol
S — Non-Dim
A — Analogue (0-10v)
P — Phase
D — DALI
B — Bluetooth**

Emergency Options: [ ]

Emergency
E — Maintained 3hr Emergency
ED — Maintained 3hr DALI Self Test
ES — Maintained 3hr Self Test

Copyright © 2025 Lucent Lighting Ltd.

Finish selection




Antique Brass



Antique Bronze



Polished Brass



Polished Nickel




Polished Chrome

Accessories




Honeycomb Louvre



Diffusing Lens



Frosted Lens



Heavy Spread Lens



Linear Spread Lens

Accessories Order Code:

Louvre/Lens

LL45	Honeycomb Louvre
LLDF	Diffusing Lens
LLFR	Frosted Lens
LLLS	Linear Spread Lens
LLHS	Heavy Spread Lens

Copyright © 2025 Lucent Lighting Ltd.

Technical Details

*Custom RAL code must be specified. Custom RAL colours can increase prices and lead times

Dimming. Whilst Lucent can offer the majority of its luminaires with various dimming options, it remains the responsibility of the specifier/installer to check and ensure compatibility of any control equipment used. Additional cabling may be required depending on the dimming protocol specified.

**Bluetooth (wireless) is the communication method. The exact dimming protocol must be confirmed to allow the selection of suitable drivers or bluetooth devices.

^ Depth indicated is the minimum recess depth for the luminaire with a remote mounted LED driver. Installing a driver through either the luminaire cut-out or installation kit may require additional recess depth, please refer to the relevant luminaire installation instructions for further details.Data correct at time of publishing

First Fix Requirement. Luminaire comprised of fixture body with ceiling trim and installation kit, which is to be fitted into the ceiling once finished. Ensure correct alignment of the installation kit before final assembly (see luminaire instllation instructions for details)

IP Rating. Tested from underside of the ceiling

Note that the picture of the finishes provided is for illustrative purposes only. The finishes may vary in colour, texture and appearance. Contact Lucent lighting Ltd for more information.

It is the policy of Lucent Lighting to continually review and improve its products and therefore reserve the right to change any details of product or withdraw specifications without prior notice.

Luminaires designed to comply with EN60598 and all other standards.

This specification sheet supersededs all previous versions.

All intellectual property rights pertaining to the product described above and to this document are owned by or licensed to Lucent Lighting Ltd.

We reserve the right to take whatever action is necessary to protect those intellectual property rights.

Please notify Lucent Lighting Ltd of any inaccuracies immediately. E&OE