lucent®

Light efficiency:


62 Lumen/Watt

Light quality:

CRI: 92.0

Color temperature:

3123 K



Product name:

31600-LED-WW - LED51_Q-HE-30-WFL-SF - 200mA


Item number:

Duo Wallwash - LED51/Q-HE-30-WFL-SF - 200mA


Delivered information for above fixture and LED combination.

Output: 499 Lumen Peak intensity: 492 cd Power consumption: 8.0


CRI R values



TM30 C Values




Color vector graphics



Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color diviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3123 K	92.0	58.5	91.2	99.6	90.8	0.432	0.409	0.245	0.348	0.0027

Beam details



Beam angels

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
57.9°	101.9°	121.7°

Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
492 cd	96.3%	78.5%

Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
270lx	67lx	30lx	17lx	11lx	7lx	6lx	4lx	3lx	3lx	2lx	2lx	2lx	1lx	1lx	1lx	1lx	1lx	1lx	1lx
25.1fcd	6.3fcd	2.8fcd	1.6fcd	1fcd	0.7fcd	0.5fcd	0.4fcd	0.3fcd	0.3fcd	0.2fcd	0.2fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd

The above information is for 3000K colour temperature, for specific module information please see LED spec located on our website.

For information regarding other colour temperatures please refer to ies/ldt files available on the website.