

Light efficiency:


75 Lumen/Watt

Light quality:

CRI: 92.3

Color temperature:

3000 K



Product name:

**Soft 70 Accent - LED51 GEN2,
3000K, 12°, 350mA**


Item number:

073-LED51/2-30-12-350mA


**Delivered information for above
fixture and LED combination.**

Output: 1016 Lumen Peak intensity: 13104 cd Power consumption: 13.6


CRI R values



TM30 C Values




Color vector graphics



Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3000 K	92.3	58.6	90.8	99.7	90.8	0.437	0.404	0.250	0.348	0.0010

Beam details



Beam angels

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
12.3°	25.7°	38.9°

Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
13104 cd	97.9%	95.8%

Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
13104lx	3276lx	1456lx	819lx	524lx	364lx	267lx	205lx	162lx	131lx	108lx	91lx	78lx	67lx	58lx	51lx	45lx	40lx	36lx	33lx
1217.4fcd	304.3fcd	135.3fcd	76.1fcd	48.7fcd	33.8fcd	24.8fcd	19fcd	15fcd	12.2fcd	10.1fcd	8.5fcd	7.2fcd	6.2fcd	5.4fcd	4.8fcd	4.2fcd	3.8fcd	3.4fcd	3fcd

The above information is for 3000K colour temperature, for specific module information please see LED spec located on our website

For information regarding other colour temperatures please use the following factors for lumen output and candelas:

2700K = 1

4000K = 1.084