
## lucent®

#### ProSpex MiniTRIM Round Accent



86mm (3.39") overall diameter. Up to 25° tilt. Range of soft appearance with minimal trim for achieving trimless effect. Family of matching products also available. Required depth height + 25mm^



863-GU Cut-out 81mm Ø

Light Source

Max Power Lamp Base Voltage Insulation Class GU10 Halogen GU10 LED 50W (Halogen) GU10 220-240v 50/60Hz I


# lucent

Project	Ref:	
,		

Location Ref:\_

Fixture Or	der Code:	863	-GU	] – [	
Fixture 863-GU	MiniTRIM Rou	Ind Accen	t with GL	J10	
Finish WH BK RAL	White Black Custom RAL (	Colour*			]

### lucent<sub>®</sub>



Accessories: MiniTrim accepts only 1 accessory

#### Technical Details

\*Custom RAL code must be specified. Custom RAL colours can increase prices and lead times

Dimming. Whilst Lucent can offer the majority of its luminaires with various dimming options, it remains the responsibility of the specifier/installer to check and ensure compatibility of any control equipment used. Additional cabling may be required depending on the dimming protocol specified.

\*\*Bluetooth (wireless) is the communication method. The exact dimming protocol must be confirmed to allow the selection of suitable drivers or bluetooth devices.

^ Depth indicated may vary depending on lamp type used

First Fix Requirement. Luminaire comprised of fixture body with ceiling trim and installation kit, which is to be fitted into the ceiling once finished. Ensure correct alignment of the installation kit before final assembly (see luminaire instllation instructions for details)

IP Rating. Tested from underside of the ceiling

It is the policy of Lucent Lighting to continually review and improve its products and therefore reserve the right to change any details of product or withdraw specifications without prior notice.

Luminaires designed to comply with EN60598 and all other standards.

This specification sheet supersededs all previous versions.

All intellectual property rights pertaining to the product described above and to this document are owned by or licensed to Lucent Lighting Ltd.

We reserve the right to take whatever action is necessary to protect those intellectual property rights.

Please notify Lucent Lighting Ltd of any inaccuracies immediately. E&OE