

Light efficiency:


40 Lumen/Watt

Light quality:

CRI: 91.5

Color temperature:

3000 K



Product name:

31600-LED - LED51TW-5020-25 @ 3000K


Item number:

Duo Fixed - LED51TW-5020-25 @ 3000K


Delivered information for above fixture and LED combination.

Output: 609 Lumen Peak intensity: 2247 cd Power consumption: 15.1


CRI R values



TM30 C Values




Color vector graphics



Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3000 K	91.5	78.3	93.5	106.8	93.5	0.437	0.404	0.257	0.336	-0.0129

Beam details



Beam angels

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
25.4°	51.9°	75.8°

Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
2247 cd	99.9%	98.2%

Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
2243lx	561lx	249lx	140lx	90lx	62lx	46lx	35lx	28lx	22lx	19lx	16lx	13lx	11lx	10lx	9lx	8lx	7lx	6lx	6lx
208.4fcd	52.1fcd	23.2fcd	13fcd	8.3fcd	5.8fcd	4.3fcd	3.3fcd	2.6fcd	2.1fcd	1.7fcd	1.4fcd	1.2fcd	1.1fcd	0.9fcd	0.8fcd	0.7fcd	0.6fcd	0.6fcd	0.5fcd

All the above information for fixtures with LED51TW-5020 modules are tested at 3000K

Factors to adjust lumen output for the following CCTs at 100% output for the colour are as follows:

2000K = 0.67

2700K = 0.84

3500K = 1.085

4000K = 1.113

5000K = 1.087