

Light efficiency:


71 Lumen/Watt

Light quality:

CRI: 91.7

Color temperature:

3000 K



Product name:

**TubeLED Mini GEN2
3000K 38° 350mA**


Item number:

7100/2-30-38-350mA


**Delivered information for
above fixture and LED
combination.**

Output: 963 Lumen Peak intensity: 3402 cd Power consumption: 13.6


CRI R values



TM30 C Values




Color vector graphics



Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3000 K	91.7	57.9	91.3	99.3	90.3	0.437	0.404	0.251	0.348	0.0010

Beam details



Beam angels

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
30.6°	47.7°	63.3°

Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
3402 cd	99.7%	99.2%

Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
3402lx	851lx	378lx	213lx	136lx	95lx	69lx	53lx	42lx	34lx	28lx	24lx	20lx	17lx	15lx	13lx	12lx	11lx	9lx	9lx
316.1fcd	79fcd	35.1fcd	19.8fcd	12.6fcd	8.8fcd	6.5fcd	4.9fcd	3.9fcd	3.2fcd	2.6fcd	2.2fcd	1.9fcd	1.6fcd	1.4fcd	1.2fcd	1.1fcd	1fcd	0.9fcd	0.8fcd

The above information is for 3000K colour temperature, for specific module information please see LED spec located on our website

For information regarding other colour temperatures please use the following factors for lumen output and candelas:

2700K = 1

4000K = 1.084