



Pinhole4.25 Accent




Pinhole4.25 provides high performance electronics and architectural aesthetics in 4.25” trim with a 1.73” aperture. Pinhole products include adjustable, fixed and washlight in a flanged or trimless installation kit. Tray, retrofit and housing installation methods (NIC, IC, AT, T24 and CCEA) Multiple configurations for equal spacing also available. Lucent modules available in a wide range of color temperatures, beam angles, intensities, and effects (Ambiance WarmDim and Dynamic Tuneable White). MR16 and GU10 LED lamp options available. TRIAC/Phase, 0-10v/1-10v, DMX and DALI/ Digital dimming.



A30413-A-LED + 3000-PBZ  
360° rotation. Up to 30° tilt.  
Cut-out 103mm (4.00”) Ø



Installation kit for overlap flange  
3000-PBZ



A30413-A-LED + 3000-PCZ  
360° rotation. Up to 30° tilt.  
Cut-out 98mm (3.85”) Ø



Mud-in kit for seamless/trimless  
3000-PCZ

LED Source	LED51TW	LED51TW
CCT (5000K - 2000K)	@ 3000K	@ 3000K
Drive Current (max per channel)	700mA	700mA
Power inc Driver	15.1W	15.1W
Beam Angle	25°	35°
Delivered Lumens	541	635
Delivered Intensisty cd	2223	1343
Efficacy lm/w	36	42
Forward Volt (max per channel)	18.4V	18.4V
CRI	≥95 CRI	≥95 CRI

Project Ref: \_\_\_\_\_ Location Ref: \_\_\_\_\_

Specify fixture part number (All boxes must be filled in to correctly order)

A30413-A-LED					LED5ITW	5020								
--------------	--	--	--	--	---------	------	--	--	--	--	--	--	--	--

Finish \_\_\_\_\_  
WH White  
BK Black

Location \_\_\_\_\_  
XX Dry  
DP Damp  
WT Wet

Installation \_\_\_\_\_  
PB 3000-PBZ Flange kit  
PC 3000-PCZ Mud-in kit

Ceiling Thickness \_\_\_\_\_  
SC Standard Ceiling (1/2"-5/8"-3/4")  
C Custom

LED Type \_\_\_\_\_  
LED5ITW LED5ITW (95CRI)

CCT \_\_\_\_\_  
5020 5000K - 2000K

Beam Angles \_\_\_\_\_  
25 25  
35 35

Housing/Tray \_\_\_\_\_  
LMT-13-NIC Mounting Tray Non-Insulated ceilings  
LH-6.75-NIC Housing 6.75" Non-Insulated ceilings  
LH-8.50-AT/IC Housing 8.50" Insulated/Air-tight ceilings and Chicago Plenum

Mounting Hardware \_\_\_\_\_  
09 9" to 15.25" - Adjustable Bar Hanger Lengths  
14 14" to 24" - Adjustable Bar Hanger Lengths  
36 28" to 36" - Adjustable Bar Hanger Lengths  
BB Butterfly Bracket  
CB Caterpillar Bracket

Supply Voltage \_\_\_\_\_  
120 120V  
277 277V


Dimming Protocol \_\_\_\_\_  
A2 Analogue (0-10V) 2-Channel (0.1% Dimming)  
D6 DALI Type 6\*\* (0.1% Dimming)  
D8 DALI Type 8\*\* (0.1% Dimming)  
L Lutron (Consult Factory)

Emergency  
E 3hr Emergency  
ES 3hr Self Test


Louvre/Lens  
XX Not required  
LL45 Honeycomb  
LLCC Warm Tone  
LLUV UV  
LLDF Solite/Diffusing  
LLFR Frosted Lens  
LLLS Linear Spread  
LLHS Heavy Spread

\*Refer to Technical Details for more information

Housing dimensions




LH-6.75  
Non-insulated ceilings




LH-8.50  
Insulated/air-tight ceilings and  
Chicago Plenum


Tray dimensions



LMT-13  
Non-insulated ceilings



**Honeycomb Louvre (LL45)**



**Solite/Diffusing Lens (LLDF)**



**Frosted Lens (LLFR)**



**Heavy Spread Lens (LLHS)**



**Linear Spread Lens (LLLS)**



**Warm Tone (LLCC)**

Technical Details

\*Custom color requires a paint chip or RAL code and may increase price and lead-time

It is the responsibility of the specifier/integrator/installer to check and ensure compatibility of any control equipment used. Additional cabling may be required depending on the dimming protocol specified.

\*\*DALI Type 6 requires two DALI addresses, one for CCT control the other for intensity control. DALI Type 8 is a single DALI Type 8 address for CCT and intensisty control. Please check which control system is being used before specifying.

^ Depth indicated is the minimum recess depth for the luminaire with a remote mounted LED driver. Installing a driver through either the luminaire cut-out or installation kit may require additional recess depth, please refer to the relevant installation instructions prior to purchase.

First Fix Requirement. Luminaire comprised of fixture body with ceiling trim and installation kit, which is to be fitted into the ceiling once finished. Ensure correct alignment of the installation kit before final assembly (see luminaire installation instructions for details)

Location. Tested from underside of the ceiling.

Data correct at time of publishing. It is the policy of Lucent Lighting to continually review and improve its products and therefore reserve the right to change any details of product or withdraw specifications without prior notice.

This specification sheet supersedes all previous versions.

All intellectual property rights pertaining to the product described above and to this document are owned by or licensed to Lucent Lighting, Incorporated. Lucent Lighting reserves the right to take whatever action is necessary to protect its intellectual property, patents and trademarks

Please notify Lucent Lighting Inc. in accuracies. E&OE



## Light efficiency:


**36 Lumen/Watt**

## Light quality:

**CRI: 91.3**

## Color temperature:

**3000 K**



## Product name:

**Pinhole4.25 Fixed/Accent - LED51TW-5020-25 @ 3000K**


## Item number:

**A30413-F/A-LED - LED51TW-5020-25 @ 3000K**


**Delivered information for above fixture and LED combination.**

**Output: 541 Lumen Peak intensity: 2223 cd Power consumption: 15.1**


## CRI R values



## TM30 C Values




## Color vector graphics



Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3000 K	91.3	78.1	93.5	106.9	93.4	0.437	0.404	0.258	0.336	-0.0131

## Beam details



## Beam angels

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
24.1°	50°	68.8°

## Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
2223 cd	99.8%	98.8%

## Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
2223lx	556lx	247lx	139lx	89lx	62lx	45lx	35lx	27lx	22lx	18lx	15lx	13lx	11lx	10lx	9lx	8lx	7lx	6lx	6lx
206.5fcd	51.6fcd	22.9fcd	12.9fcd	8.3fcd	5.7fcd	4.2fcd	3.2fcd	2.5fcd	2.1fcd	1.7fcd	1.4fcd	1.2fcd	1.1fcd	0.9fcd	0.8fcd	0.7fcd	0.6fcd	0.6fcd	0.5fcd

All the above information for fixtures with LED51TW-5020 modules are tested at 3000K

Factors to adjust lumen output for the following CCTs at 100% output for the colour are as follows:

2000K = 0.67

2700K = 0.84

3500K = 1.085

4000K = 1.113

5000K = 1.087

Light efficiency:


**42 Lumen/Watt**

Light quality:

**CRI: 91.5**

Color temperature:

**3000 K**



Product name:

**Pinhole4.25 Fixed/Accent - LED51TW-5020-35 @ 3000K**


Item number:

**A30413-F/A-LED - LED51TW-5020-35 @ 3000K**


**Delivered information for above fixture and LED combination.**

**Output: 635 Lumen Peak intensity: 1343 cd Power consumption: 15.1**


CRI R values



TM30 C Values




Color vector graphics



Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3000 K	91.5	77.0	93.6	106.5	93.8	0.437	0.404	0.255	0.335	-0.0129

## Beam details



## Beam angels

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
38.3°	66.9°	85°

## Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
1343 cd	99.8%	98.2%

## Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
1343lx	336lx	149lx	84lx	54lx	37lx	27lx	21lx	17lx	13lx	11lx	9lx	8lx	7lx	6lx	5lx	5lx	4lx	4lx	3lx
124.7fcd	31.2fcd	13.9fcd	7.8fcd	5fcd	3.5fcd	2.5fcd	1.9fcd	1.5fcd	1.2fcd	1fcd	0.9fcd	0.7fcd	0.6fcd	0.6fcd	0.5fcd	0.4fcd	0.4fcd	0.3fcd	0.3fcd

All the above information for fixtures with LED51TW-5020 modules are tested at 3000K

Factors to adjust lumen output for the following CCTs at 100% output for the colour are as follows:

2000K = 0.67

2700K = 0.84

3500K = 1.085

4000K = 1.113

5000K = 1.087