
ProSpex Plus Mini Round Wallwash Trimless

TM65.2	11kgCO2e
TM66	2.3 CEAM



80mm (3.15”) overall trimless diameter. Available with standard trim kit or plaster-in kit options. Family of matching products also available.



750+LED-TL/PCZ-WW
Cut-out Ø82mm
Trimless Kit
Required dept height+25mm^

LED Source	LED51/3-TW	
CRI	≥90 CRI	
Drive Current	350mA	
Power inc Driver	15.4W	
Beam Angle	Wallwash	
Forward Volt	36V	
CCT	6527	4018
Delivered Lumens	840	760
Delivered Intensisty cd	534	485
Delivered Lumens per circuit watt	55	49

L1
≥75 Dwellings Compliant

Copyright © 2025 Lucent Lighting Ltd.

Project Ref:_____ Location Ref:_____

Fixture Order Code: 750+LED-TL-WW – [ ] – [ ] – [ ]

Fixture
750+LED-TL-WW Plus Mini Conical Wallwash Trimless with LED51


Installation
750+TL TL trimless kit
750+PCZ PCZ Plaster kit

Finish
WH White RAL 9010
BK Black RAL 9005
RAL* Custom RAL Colour*
ABR1 Antique Brass
ABZ1 Antique Bronze
PCH1 Polished Chrome
PNK1 Polished Nickel
PBR1 Polished Brass

IP Rating
44 IP44
54 IP54



750+PCZ
Trimless Kit
Front fitting, full skim



750+TL
Trimless Kit
Rear fitting, partial skim

Module Order Code: LED51/Q-HE – [ ] – WFL

LED
LED51/Q-HE LED50 ONE QUANTUM High Efficacy

CCT
27 2700K
30 3000K
40 (3) 4000K

Beam
WFL Wide Flood

(3) contact Lucent for availability

Driver Options: [ ]

Protocol
S Non-Dim
A Analogue (0-10v)
P Phase
D DALI
B Bluetooth**

Emergency Options: [ ]

Emergency
E Maintained 3hr Emergency
ED Maintained 3hr DALI Self Test
ES Maintained 3hr Self Test

Copyright © 2025 Lucent Lighting Ltd.

Finish selection




Antique Brass



Antique Bronze



Polished Brass



Polished Nickel



Polished Chrome

Copyright © 2025 Lucent Lighting Ltd.

LED51/3-TW Factor and Wattage Information

All values given on page 1 and ies/ldt files are at the highest colour temperature. Use the below factors and wattages to calculate lumen output for other standard colour temperatures.

	LED51/3-TW-6527		LED51/3-TW-4018	
CCT	Lm Factor	System Wattage	Lm Factor	System Wattage
6500K	1.00	15.4		
5000K	1.06	14.7		
4000K	1.08	13.6	1.00	15.4
3000K	0.83	15.4	0.90	13.6
2700K	0.63	17	0.82	13.2
2400K			0.76	13.5
2200K			0.71	14
1800K			0.59	15.1

Technical Details

*Custom RAL code must be specified. Custom RAL colours can increase prices and lead times

Dimming. Whilst Lucent can offer the majority of its luminaires with various dimming options, it remains the responsibility of the specifier/installer to check and ensure compatibility of any control equipment used. Additional cabling may be required depending on the dimming protocol specified.

**DALI Type 6 requires two DALI addresses, one for CCT control the other for Intesisty control. DALI Type 8 is a single DALI Type 8 address for CCT and Intesisty control. Please check which control system is being used before specifying.

**Bluetooth (wireless) is the communication method. The exact dimming protocol must be confirmed to allow the selection of suitable drivers or bluetooth devices.

^ Depth indicated is the minimum recess depth for the luminaire with a remote mounted LED driver. Installing a driver through either the luminaire cut-out or installation kit may require additional recess depth, please refer to the relevant luminaire installation instructions for further details.Data correct at time of publishing

First Fix Requirement. Luminaire comprised of fixture body with ceiling trim and installation kit, which is to be fitted into the ceiling once finished. Ensure correct alignment of the installation kit before final assembly (see luminaire instllation instructions for details)

IP Rating. Tested from underside of the ceiling

Note that the picture of the finishes provided is for illustrative purposes only. The finishes may vary in colour, texture and appearance. Contact Lucent lighting Ltd for more information.

It is the policy of Lucent Lighting to continually review and improve its products and therefore reserve the right to change any details of product or withdraw specifications without prior notice.

Luminaires designed to comply with EN60598 and all other standards.

This specification sheet supersededs all previous versions.

All intellectual property rights pertaining to the product described above and to this document are owned by or licensed to Lucent Lighting Ltd.

We reserve the right to take whatever action is necessary to protect those intellectual property rights.

Please notify Lucent Lighting Ltd of any inaccuracies immediately. E&OE