
ProSpex Plus Mini Round Wallwash Trim

TM65.2	11kgCO2e
TM66	2.3 CEAM



90mm (3.54”) overall trim diameter. Available with standard trim kit or plaster-in kit for flush appearance. Family of matching products also available.



LED Source	LED51/3-TW
CRI	≥90 CRI
Drive Current	350mA
Power inc Driver	15.4W
Beam Angle	Wallwash
Forward Volt	36V
CCT	6527 4018
Delivered Lumens	840 760
Delivered Intensisty cd	534 485
Delivered Lumens per circuit watt	55 49

Copyright © 2025 Lucent Lighting Ltd.

Project Ref:_____ Location Ref:_____

Fixture Order Code: 750+LED-TR-WW – [ ] – [ ]

Fixture
750+LED-TR-WW Plus Mini Round Wallwash Trim with LED51

Finish
WH	White RAL 9010
BK	Black RAL 9005
RAL*	Custom RAL Colour*
ABR1	Antique Brass
ABZ1	Antique Bronze
PCH1	Polished Chrome
PNK1	Polished Nickel
PBR1	Polished Brass

IP Rating
54 IP54



Module Order Code: LED51/3-TW – [ ] – [ ]

LED
LED51/3-TW LED50 ONE Gen3 Dynamic Tuneable White

CCT
4018	4000K - 1800K
6527	6500K - 2700K

Beam
NF	Narrow Flood
FL	Flood
WFL	Wide Flood

Driver Options: [ ]

Protocol
D6	DALI Type 6**
D8	DALI Type 8**
B	Bluetooth***

Emergency Options: [ ]

Emergency
E	Maintained 3hr Emergency
ED	Maintained 3hr DALI Self Test
ES	Maintained 3hr Self Test

Copyright © 2025 Lucent Lighting Ltd.

Finish selection




Antique Brass



Antique Bronze



Polished Brass



Polished Nickel



Polished Chrome

Copyright © 2025 Lucent Lighting Ltd.

LED51/3-TW Factor and Wattage Information

All values given on page 1 and ies/ldt files are at the highest colour temperature. Use the below factors and wattages to calculate lumen output for other standard colour temperatures.

	LED51/3-TW-6527		LED51/3-TW-4018	
CCT	Lm Factor	System Wattage	Lm Factor	System Wattage
6500K	1.00	15.4		
5000K	1.06	14.7		
4000K	1.08	13.6	1.00	15.4
3000K	0.83	15.4	0.90	13.6
2700K	0.63	17	0.82	13.2
2400K			0.76	13.5
2200K			0.71	14
1800K			0.59	15.1

Technical Details

*Custom RAL code must be specified. Custom RAL colours can increase prices and lead times

Dimming. Whilst Lucent can offer the majority of its luminaires with various dimming options, it remains the responsibility of the specifier/installer to check and ensure compatibility of any control equipment used. Additional cabling may be required depending on the dimming protocol specified.

**DALI Type 6 requires two DALI addresses, one for CCT control the other for Intesisty control. DALI Type 8 is a single DALI Type 8 address for CCT and Intesisty control. Please check which control system is being used before specifying.

**Bluetooth (wireless) is the communication method. The exact dimming protocol must be confirmed to allow the selection of suitable drivers or bluetooth devices.

^ Depth indicated is the minimum recess depth for the luminaire with a remote mounted LED driver. Installing a driver through either the luminaire cut-out or installation kit may require additional recess depth, please refer to the relevant luminaire installation instructions for further details.Data correct at time of publishing

First Fix Requirement. Luminaire comprised of fixture body with ceiling trim and installation kit, which is to be fitted into the ceiling once finished. Ensure correct alignment of the installation kit before final assembly (see luminaire instllation instructions for details)

IP Rating. Tested from underside of the ceiling

Note that the picture of the finishes provided is for illustrative purposes only. The finishes may vary in colour, texture and appearance. Contact Lucent lighting Ltd for more information.

It is the policy of Lucent Lighting to continually review and improve its products and therefore reserve the right to change any details of product or withdraw specifications without prior notice.

Luminaires designed to comply with EN60598 and all other standards.

This specification sheet supersededs all previous versions.

All intellectual property rights pertaining to the product described above and to this document are owned by or licensed to Lucent Lighting Ltd.

We reserve the right to take whatever action is necessary to protect those intellectual property rights.

Please notify Lucent Lighting Ltd of any inaccuracies immediately. E&OE